



Ultrasonics and 3D Printing

Branson introduces an innovative solution to remove support material from 3D-printed parts.

Branson's CPXH series ultrasonic cleaner offers the ideal way to remove support material from fused deposition modeling 3D-printed parts. The application of ultrasonic energy accelerates the removal of support material, drastically reducing post-processing time, and expediting the prototyping process. Further, the Bransonic ultrasonic bath utilizes the same solution used in other support removal baths.

With its fully programmable interface, the Bransonic CPXH series digital bath is the most advanced ultrasonic bath yet. It features the benefits of heated cleaning with the ability to set temperatures from 20°C/68°F to 69°C/156°F. Plus, you get complete digital control and self-adaptive technology for consistent, worry-free operation — every time.

Features:

- Special lid to submerge 3D-printed parts
- Heated cleaning – up to 69°C/156°F
- Fully programmable
- High/low power control
- Degas mode
- Sleep mode



ORDERING INFORMATION:

	Part No.
Model 8800 – Digital, Heated	CPX-952-818R (120V) CPX-952-838R (240V)
Special Lid to submerge 3D-printed parts:	100-032-551
Perforated tray:	100-410-168

SPECIFICATIONS

Model 8800	
Tank Capacity	
Litres/Gallons	20.8/5.5
Tank Size (L/W/D)	
Inches	19.5 x 11.5 x 6
mm	495 x 466 x 391
Overall Size (L.W.D)	
Inches	23.5 x 18.3 x 15.4
mm	596 x 466 x 391
Weight	
Pounds/Kilograms	26/11.8
Frequency	40 kHz
Drain	Yes

Americas

Branson Ultrasonics Corp.
41 Eagle Road
Danbury, CT 06813-1961
T: 800-796-0400
F: 203-796-9838
www.bransonultrasonics.com

Europe

Branson Ultraschall
Niederlassung der Emerson
Technologies GmbH & Co. OHG
Waldstrasse 53-55
63128 Dietzenbach, Germany
T: +49-6074-497-0
F: +49-6074-497-199
www.branson.eu

Asia

Branson Ultrasonics (Shanghai) Co., Ltd.
758 Rong Le Dong Road
Song Jiang, Shanghai, PRC, 201613
T: 86-21-3781-0588
F: 86-21-5774-5100
www.branson.com.cn